

Lecture 25 – Type Inference (1)

COSE212: Programming Languages

Jihyeok Park



2023 Fall

- **Polymorphism** is to use a single entity as **multiple types**, and there are various kinds of polymorphism:
 - **Parametric polymorphism**
 - **Subtype polymorphism**
 - **Ad-hoc polymorphism**
 - ...
- **PTFAE** – TFAE with **parametric polymorphism**.
- **STFAE** – TFAE with **subtype polymorphism**.

- **Polymorphism** is to use a single entity as **multiple types**, and there are various kinds of polymorphism:
 - **Parametric polymorphism**
 - **Subtype polymorphism**
 - **Ad-hoc polymorphism**
 - ...
- **PTFAE** – TFAE with **parametric polymorphism**.
- **STFAE** – TFAE with **subtype polymorphism**.
- In this lecture, we will learn **type inference**.

Definition (Type Inference)

Type inference is the process of automatically inferring the types of expressions.

Definition (Type Inference)

Type inference is the process of automatically inferring the types of expressions.

The goal of **type inference algorithm** is to infer the type of an expression without **explicit type annotations** given by programmers.

Definition (Type Inference)

Type inference is the process of automatically inferring the types of expressions.

The goal of **type inference algorithm** is to infer the type of an expression without **explicit type annotations** given by programmers.

Let's consider the following RFAE expression:

```
/* RFAE */  
def sum(x) = if (x < 1) 0 else x + sum(x - 1)  
sum
```

How can we **automatically infer** the type of sum?

Definition (Type Inference)

Type inference is the process of automatically inferring the types of expressions.

The goal of **type inference algorithm** is to infer the type of an expression without **explicit type annotations** given by programmers.

Let's consider the following RFAE expression:

```
/* RFAE */  
def sum(x) = if (x < 1) 0 else x + sum(x - 1)  
sum
```

How can we **automatically infer** the type of sum?

- 1 Introduce **type variables** to denote unknown types
- 2 Collect the **type constraints** on the types
- 3 Find a **solution** (substitution of type variables) to the constraints

1. Example 1 – sum

2. Example 2 – app


3. Example 3 – id

1. Example 1 – sum

2. Example 2 – app

3. Example 3 – id


Example 1 – sum



Type Environment

X	T
x	???
sum	???

Example 1 – sum



Type Environment


X	T
x	$T1$
sum	$T1 \Rightarrow T2$

Solution

X_α	T
$T1$	-
$T2$	-

Let's define **type variables** for unknown types.

Example 1 – sum




Type Environment

X	T
x	$T1$
sum	$T1 \Rightarrow T2$

Solution

X_α	T
$T1$	-
$T2$	-

Example 1 – sum




Type Environment

X	T
x	$T1$
sum	$T1 \Rightarrow T2$

Solution

X_α	T
$T1$	-
$T2$	-



Type Environment


X	T
x	$T1$
sum	$T1 \Rightarrow T2$

Solution

X_α	T
$T1$	$Number$
$T2$	$-$

The **operands** of $<$ must be of type **Number**.
 So, we collected a **type constraint**: $T1 == Number$.

Example 1 – sum




Type Environment

X	T
x	$T1$
sum	$T1 \Rightarrow T2$

Solution

X_α	T
$T1$	$Number$
$T2$	$-$

Example 1 – sum




Type Environment

X	T
x	T1
sum	T1 \Rightarrow T2

Solution

X_α	T
T1	Number
T2	-

Example 1 – sum




Type Environment

X	T
x	$T1$
sum	$T1 \Rightarrow T2$

Solution

X_α	T
$T1$	Number
$T2$	-

Example 1 – sum




Type Environment

X	T
x	$T1$
sum	$T1 \Rightarrow T2$

Solution

X_α	T
$T1$	$Number$
$T2$	$-$

Example 1 – sum




Type Environment

X	T
x	$T1$
sum	$T1 \Rightarrow T2$

Solution

X_α	T
$T1$	$Number$
$T2$	$-$

Example 1 – sum



Type Environment


X	T
x	$T1$
sum	$T1 \Rightarrow T2$

Solution

X_α	T
$T1$	$Number$
$T2$	$-$

The **operands** of $-$ must be of type **Number**.
We collected a **type constraint**: $T1 == Number$.
But, it is not a new constraint.

Example 1 – sum



Type Environment

X	T
x	$T1$
sum	$T1 \Rightarrow T2$

Solution


X_α	T
$T1$	$Number$
$T2$	$-$

The **argument type** should be equal to the **parameter type**.

We collected a **type constraint**: $T1 == Number$.

Again, it is not a new constraint.

Example 1 – sum



Type Environment

X	T
x	$T1$
sum	$T1 \Rightarrow T2$

Solution


X_α	T
$T1$	$Number$
$T2$	$Number$

The **operands** of $+$ must be of type **Number**.

We collected **type constraints**: $T1 == Number$ and $T2 == Number$.

The second one is a new constraint!

Example 1 – sum




Type Environment

X	T
x	$T1$
sum	$T1 \Rightarrow T2$

Solution

X_α	T
$T1$	Number
$T2$	Number



Type Environment

X	T
x	$T1$
sum	$T1 \Rightarrow T2$

Solution

X_α	T
$T1$	$Number$
$T2$	$Number$

The type of sum is $T1 \Rightarrow T2$. Using the solution inferred by the collected constraints, we can instantiate it to $Number \Rightarrow Number$.

1. Example 1 – sum


2. Example 2 – app


3. Example 3 – id

Example 2 – app

Let's infer the type of the following RFAE expression:

```
/* RFAE */  
val app = n => f => f(n)  
app(42)(x => x)
```






Type Environment

X	T
n	$T1$

Solution

X_α	T
$T1$	-

Let's define a new **type variable T1** for the parameter n .




Type Environment

X	T
<code>n</code>	$T1$
<code>f</code>	$T2$

Solution

X_α	T
$T1$	-
$T2$	-

Let's define a new **type variable $T2$** for the parameter `f`.




Type Environment

X	T
n	$T1$
f	$T2$

Solution

X_α	T
$T1$	-
$T2$	-




Type Environment

X	T
n	$T1$
f	$T2$

Solution

X_α	T
$T1$	-
$T2$	-



Type Environment

X	T
n	$T1$
f	$T2$


Solution

X_α	T
$T1$	-
$T2$	$T1 \Rightarrow T3$
$T3$	-

The type $T2$ of f should be in the form of $T1 \Rightarrow ???$.

Let's define a new **type variable** $T3$ for $???$ (the return type of f).

So, we collected a **type constraint**: $T2 == T1 \Rightarrow T3$.




Type Environment

X	T
n	$T1$

Solution

X_α	T
$T1$	-
$T2$	$T1 \Rightarrow T3$
$T3$	-




Type Environment

X	T

Solution

X_α	T
$T1$	-
$T2$	$T1 \Rightarrow T3$
$T3$	-

Example 2 – app




Type Environment

X	T
app	$T1 \Rightarrow T2 \Rightarrow T3$

Solution

X_α	T
T1	-
T2	$T1 \Rightarrow T3$
T3	-

Example 2 – app




Type Environment

X	T
app	$T1 \Rightarrow T2 \Rightarrow T3$

Solution

X_α	T
T1	-
T2	$T1 \Rightarrow T3$
T3	-

Example 2 – app




Type Environment

X	T
app	$T1 \Rightarrow T2 \Rightarrow T3$

Solution

X_α	T
$T1$	-
$T2$	$T1 \Rightarrow T3$
$T3$	-



Type Environment


X	T
app	$T1 \Rightarrow T2 \Rightarrow T3$

Solution

X_α	T
$T1$	Number
$T2$	$T1 \Rightarrow T3$
$T3$	-

The **parameter type** $T1$ should be equal to the **argument type** **Number**.
 So, we collected a **type constraint**: $T1 == \text{Number}$.

Example 2 – app



Type Environment


X	T
app	$T1 \Rightarrow T2 \Rightarrow T3$
x	$T4$

Solution

X_α	T
T1	Number
T2	$T1 \Rightarrow T3$
T3	-
T4	-

Let's define a new **type variable T4** for the parameter x.

Example 2 – app




Type Environment

X	T
app	$T1 \Rightarrow T2 \Rightarrow T3$
x	$T4$

Solution

X_α	T
T1	Number
T2	$T1 \Rightarrow T3$
T3	-
T4	-

Example 2 – app




Type Environment

X	T
app	$T1 \Rightarrow T2 \Rightarrow T3$
x	$T4$

Solution

X_α	T
$T1$	Number
$T2$	$T1 \Rightarrow T3$
$T3$	-
$T4$	-



Type Environment

X	T
app	$T1 \Rightarrow T2 \Rightarrow T3$
x	$T4$

Solution

X_α	T
$T1$	Number
$T2$	$T1 \Rightarrow T3$
$T3$	Number
$T4$	Number

The **parameter type** $T2$ should be equal to **argument type** $T4 \Rightarrow T4$.
 We collected **type constraints**: $T3 == \text{Number}$ and $T4 == \text{Number}$.
 Finally, the entire expression has type $T3$ ($= \text{Number}$).

1. Example 1 – sum


2. Example 2 – app


3. Example 3 – id

Example 3 – id

Let's infer the type of the following RFAE expression:

```
/* RFAE */  
val id = x => x  
val n = id(42)  
val b = id(true)  
b
```





Type Environment


X	T
x	$T1$

Solution

X_α	T
$T1$	-

Let's define a new **type variable T1** for the parameter x .

Example 3 – id




Type Environment

X	T
x	$T1$

Solution

X_α	T
$T1$	-

Example 3 – id




Type Environment

X	T

Solution

X_α	T
T1	-



Type Environment


X	T
id	$[T1] \{ T1 \Rightarrow T1 \}$

Solution

X_α	T
T1	-

Let's **generalize** the type $T1 \Rightarrow T1$ into a **polymorphic type** for `id` with **type variable** $T1$ as a **type parameter**.

We call this **let-polymorphism** because it only introduces polymorphism for the let-binding (e.g., `val`).



Type Environment


X	T
id	$[T1] \{ T1 \Rightarrow T1 \}$

Solution

X_α	T
$T1$	-
$T2$	-

Let's define a new **type variable T2** to **instantiate** the **type variable T1**.
 And, **substitute T1** with **T2**.

Example 3 – id




Type Environment

X	T
id	[T1] { T1 => T1 }

Solution

X_α	T
T1	-
T2	-




Type Environment

X	T
id	$[T1] \{ T1 \Rightarrow T1 \}$

Solution

X_α	T
T1	-
T2	Number

The **parameter type** $T2$ should be equal to **argument type** **Number**.
 We collected a **type constraint**: $T2 == \text{Number}$.




Type Environment

X	T
id	$[T1] \{ T1 \Rightarrow T1 \}$
n	$T2$

Solution

X_α	T
$T1$	-
$T2$	Number

$T2$ is not a free type variable because it actually represents **Number**.
 So, we will not introduce a polymorphic type in this case.



Type Environment


X	T
id	$[T1] \{ T1 \Rightarrow T1 \}$
n	$T2$

Solution

X_α	T
$T1$	-
$T2$	Number
$T3$	-

Let's define a new **type variable T3** to **instantiate** the **type variable T1**.
 And, **substitute T1** with **T3**.

Example 3 – id




Type Environment

X	T
id	$[T1] \{ T1 \Rightarrow T1 \}$
n	$T2$

Solution

X_α	T
$T1$	-
$T2$	Number
$T3$	-




Type Environment

X	T
id	$[T1] \{ T1 \Rightarrow T1 \}$
n	$T2$

Solution

X_α	T
$T1$	-
$T2$	Number
$T3$	Boolean

The **parameter type** $T3$ should be equal to **argument type** **Boolean**.
 We collected a **type constraint**: $T3 == \text{Boolean}$.



Type Environment


X	T
id	$[T1] \{ T1 \Rightarrow T1 \}$
n	$T2$
b	$T3$

Solution

X_α	T
$T1$	-
$T2$	Number
$T3$	Boolean

T3 is not a free type variable because it actually represents **Boolean**. So, we will not introduce a polymorphic type in this case.

Example 3 – id



Type Environment

X	T
id	$[T1] \{ T1 \Rightarrow T1 \}$
n	$T2$
b	$T3$

Solution

X_α	T
$T1$	-
$T2$	Number
$T3$	Boolean

Finally, the entire expression has type $T3$ (= **Boolean**).

1. Example 1 – sum

2. Example 2 – app

3. Example 3 – id

- Type Inference (2)

Jihyeok Park

`jihyeok_park@korea.ac.kr`

`https://plrg.korea.ac.kr`