

Lecture 9 – Recursive Functions

COSE212: Programming Languages

Jihyeok Park



2025 Fall

Recall

- Syntactic Sugar
 - FAE – Removing val from FVAE
 - Syntactic Sugar and Desugaring
- Lambda Calculus (LC)
 - Church Encodings
 - Church-Turing Thesis

Recall

- Syntactic Sugar
 - FAE – Removing val from FVAE
 - Syntactic Sugar and Desugaring
- Lambda Calculus (LC)
 - Church Encodings
 - Church-Turing Thesis
- In this lecture, we will learn **recursion** and **conditionals**.

Recall

- Syntactic Sugar
 - FAE – Removing val from FVAE
 - Syntactic Sugar and Desugaring
- Lambda Calculus (LC)
 - Church Encodings
 - Church-Turing Thesis
- In this lecture, we will learn **recursion** and **conditionals**.
- **RFAE – FAE with recursive functions**
 - Concrete and Abstract Syntax
 - Interpreter and Natural Semantics

Contents

1. Recursion and Conditionals

Recursion in F1VAE

Recursion in FAE

2. Recursion without New Syntax in FAE

`mkRec`: Helper Function for Recursion

3. RFAE – FAE with Recursion and Conditionals

Concrete Syntax

Abstract Syntax

4. Interpreter and Natural Semantics for RFAE

Interpreter and Natural Semantics

Arithmetic Comparison Operators

Conditionals

Recursive Function Definitions

Contents

1. Recursion and Conditionals

Recursion in F1VAE

Recursion in FAE

2. Recursion without New Syntax in FAE

`mkRec`: Helper Function for Recursion

3. RFAE – FAE with Recursion and Conditionals

Concrete Syntax

Abstract Syntax

4. Interpreter and Natural Semantics for RFAE

Interpreter and Natural Semantics

Arithmetic Comparison Operators

Conditionals

Recursive Function Definitions

A **recursive function** is a function that calls itself, and it is useful for **iterative processes** on **inductive data structures**.

A **recursive function** is a function that calls itself, and it is useful for **iterative processes** on **inductive data structures**.

Let's define a **recursive function** `sum` that computes the sum of integers from 1 to n in Scala:

```
/* Scala */
def sum(n: Int): Int =
  if (n < 1) 0          // base case
  else n + sum(n - 1)    // recursive case

sum(10) // 10 + 9 + 8 + 7 + 6 + 5 + 4 + 3 + 2 + 1 + 0 = 55
```

A **recursive function** is a function that calls itself, and it is useful for **iterative processes** on **inductive data structures**.

Let's define a **recursive function** `sum` that computes the sum of integers from 1 to n in Scala:

```
/* Scala */
def sum(n: Int): Int =
  if (n < 1) 0          // base case
  else n + sum(n - 1)    // recursive case

sum(10) // 10 + 9 + 8 + 7 + 6 + 5 + 4 + 3 + 2 + 1 + 0 = 55
```

For recursive functions, we need **conditionals** to define 1) **base cases** and 2) **recursive cases**.

Most programming languages support **recursive functions**:

- Scala

```
def sum(n: Int): Int = if (n < 1) 0 else n + sum(n - 1)
```

- C++

```
int sum(int n) { return n < 1 ? 0 : n + sum(n - 1); }
```

- Python

```
def sum(n): return 0 if n < 1 else n + sum(n - 1)
```

- Rust

```
fn sum(n: i32) -> i32 { if n < 1 {0} else {n + sum(n-1)} }
```

- ...

The F1VAE language already supports **recursive functions**:

```
/* F1VAE */  
def sum(n) = n + sum(n + -1);  
sum(10)
```

Why?

The F1VAE language already supports **recursive functions**:

```
/* F1VAE */  
def sum(n) = n + sum(n + -1);  
sum(10)
```

Why? The **function environment** Λ stores all the function definitions before evaluating the expressions.

$$\Lambda = [\text{sum} \mapsto \text{def sum}(n) = n + \text{sum}(n + -1)]$$

We can lookup and invoke the function `sum` in its body.

The F1VAE language already supports **recursive functions**:

```
/* F1VAE */  
def sum(n) = n + sum(n + -1);  
sum(10)
```

Why? The **function environment** Λ stores all the function definitions before evaluating the expressions.

$$\Lambda = [\text{sum} \mapsto \text{def sum}(n) = n + \text{sum}(n + -1)]$$

We can lookup and invoke the function `sum` in its body.

However, is it enough to support recursive functions?

The F1VAE language already supports **recursive functions**:

```
/* F1VAE */  
def sum(n) = n + sum(n + -1);  
sum(10)
```

Why? The **function environment** Λ stores all the function definitions before evaluating the expressions.

$$\Lambda = [\text{sum} \mapsto \text{def sum}(n) = n + \text{sum}(n + -1)]$$

We can lookup and invoke the function `sum` in its body.

However, is it enough to support recursive functions?

No! We need **conditionals** to define 1) **base cases** and 2) **recursive cases** for recursive functions. The above example causes an **infinite loop**.

Recursion in F1VAE

If we only add **conditionals** to F1VAE, we can define recursive functions in F1VAE without any more extensions for recursion.

Programs $\mathbb{P} \ni p ::= f^* e$ (Program)

Function Definitions $\mathbb{F} \ni f ::= \text{def } x(x) = e$ (FunDef)

Expressions $\mathbb{E} \ni e ::= \dots$

| $e < e$ (Lt)

| $\text{if } (e) e \text{ else } e$ (If)

Values $\mathbb{V} \ni v ::= n \mid b$

Function Environments $\Lambda \in \mathbb{X} \xrightarrow{\text{fin}} \mathbb{F}$ (FEnv)

Boolean $b \in \mathbb{B} = \{\text{true}, \text{false}\}$ (Boolean)

```
/* F1VAE + conditionals */
def sum(n) = if (n < 1) 0 else n + sum(n + -1);
sum(10) // 55
```

$$\Lambda = [\text{sum} \mapsto \text{def sum}(n) = \text{if } (n < 1) 0 \text{ else } n + \text{sum}(n + -1)]$$

Recursion in FAE

```
/* FAE + conditionals */
val sum = n => {
    if (n < 1) 0
    else n + sum(n + -1)
};
sum(10)
```

What happens if we add **conditionals** to FAE? Is the following FAE expression a recursive function?

Recursion in FAE

```
/* FAE + conditionals */
val sum = n => {
    if (n < 1) 0
    else n + sum(n + -1)
};
sum(10)
```

What happens if we add **conditionals** to FAE? Is the following FAE expression a recursive function? **No!** `sum` is a **free identifier**! Why?

Recursion in FAE

```
/* FAE + conditionals */
val sum = n => {
    if (n < 1) 0
    else n + sum(n + -1)
};
sum(10)
```

What happens if we add **conditionals** to FAE? Is the following FAE expression a recursive function? **No!** `sum` is a **free identifier**! Why?

We use **static scoping** for function definitions in FAE. At the definition site, the variable `sum` is not defined in the environment.

```
/* FAE + conditionals */  
val sum = n => {  
    if (n < 1) 0  
    else n + sum(n + -1)  
};  
sum(10)
```

What happens if we add **conditionals** to FAE? Is the following FAE expression a recursive function? **No!** `sum` is a **free identifier**! Why?

We use **static scoping** for function definitions in FAE. At the definition site, the variable `sum` is not defined in the environment.

Then, how to support recursive functions in FAE? There are two ways:

- ① **Without new syntax** – using `mkRec` to define recursive functions
- ② **With new syntax** – extending FAE with recursive function definitions

Contents

1. Recursion and Conditionals

Recursion in F1VAE

Recursion in FAE

2. Recursion without New Syntax in FAE

`mkRec`: Helper Function for Recursion

3. RFAE – FAE with Recursion and Conditionals

Concrete Syntax

Abstract Syntax

4. Interpreter and Natural Semantics for RFAE

Interpreter and Natural Semantics

Arithmetic Comparison Operators

Conditionals

Recursive Function Definitions

Recursion without New Syntax in FAE



```
/* FAE + conditionals */
val sum = n => {
    if (n < 1) 0
    else n + sum(n + -1)
};
sum(10)
```

How to let `sum` know itself in its body?

```
/* FAE + conditionals */
val sum = n => {
    if (n < 1) 0
    else n + sum(n + -1)
};
sum(10)
```

How to let `sum` know itself in its body?

Let's pass the function as an argument to itself!

Recursion without New Syntax in FAE



```
/* FAE + conditionals */  
val sumX = sumY => {  
    n => {  
        if (n < 1) 0  
        else n + sumY(sumY)(n + -1)  
    }  
};  
sumX(sumX)(10)
```

Recursion without New Syntax in FAE

```
/* FAE + conditionals */  
val sumX = sumY => {  
    n => {  
        if (n < 1) 0  
        else n + sumY(sumY)(n + -1)  
    }  
};  
sumX(sumX)(10)
```

However, it is annoying to always pass the function to itself!

```
/* FAE + conditionals */  
val sumX = sumY => {  
    n => {  
        if (n < 1) 0  
        else n + sumY(sumY)(n + -1)  
    }  
};  
sumX(sumX)(10)
```

However, it is annoying to always pass the function to itself!

Let's wrap this to get `sum` back!

Recursion without New Syntax in FAE

```
/* FAE + conditionals */
val sum = n => {
    val sumX = sumY => {
        n => {
            if (n < 1) 0
            else n + sumY(sumY)(n + -1)
        }
    };
    sumX(sumX)(n)
};

sum(10)
```

¹https://en.wikipedia.org/wiki/Lambda_calculus#%CE%B7-reduction

Recursion without New Syntax in FAE



```
/* FAE + conditionals */
val sum = n => {
    val sumX = sumY => {
        n => {
            if (n < 1) 0
            else n + sumY(sumY)(n + -1)
        }
    };
    sumX(sumX)(n)
};

sum(10)
```

We can simplify this using **η -reduction**¹:

$$e \equiv \lambda x.e(x) \quad \text{only if } x \text{ is NOT FREE in } e.$$

¹https://en.wikipedia.org/wiki/Lambda_calculus#%CE%B7-reduction

Recursion without New Syntax in FAE



```
/* FAE + conditionals */
val sum = {
    val sumX = sumY => {
        n => { // ALMOST the same as the original body
            if (n < 1) 0
            else n + sumY(sumY)(n + -1)
        }
    };
    sumX(sumX)
};
sum(10)
```

Recursion without New Syntax in FAE

```
/* FAE + conditionals */
val sum = {
    val sumX = sumY => {
        n => { // ALMOST the same as the original body
            if (n < 1) 0
            else n + sumY(sumY)(n + -1)
        }
    };
    sumX(sumX)
};
sum(10)
```

The function body is almost the same as the original version except that we need to call the function as `sumY(sumY)` instead of `sum`.

Recursion without New Syntax in FAE

```
/* FAE + conditionals */
val sum = {
    val sumX = sumY => {
        n => { // ALMOST the same as the original body
            if (n < 1) 0
            else n + sumY(sumY)(n + -1)
        }
    };
    sumX(sumX)
};
sum(10)
```

The function body is almost the same as the original version except that we need to call the function as `sumY(sumY)` instead of `sum`.

Let's define a variable `sum` to be `sumY(sumY)`!

Recursion without New Syntax in FAE

```
/* FAE + conditionals */
val sum = {
    val sumX = sumY => {
        val sum = sumY(sumY);
        n => { // EXACTLY the same as the original body
            if (n < 1) 0
            else n + sum(n + -1)
        }
    };
    sumX(sumX)
};
sum(10)
```

Recursion without New Syntax in FAE

```
/* FAE + conditionals */
val sum = {
    val sumX = sumY => {
        val sum = sumY(sumY); // INFINITE LOOP
        n => { // EXACTLY the same as the original body
            if (n < 1) 0
            else n + sum(n + -1)
        }
    };
    sumX(sumX)
};
sum(10)
```

Unfortunately, this is an **infinite loop!**

```
/* FAE + conditionals */
val sum = {
    val sumX = sumY => {
        val sum = sumY(sumY); // INFINITE LOOP
        n => { // EXACTLY the same as the original body
            if (n < 1) 0
            else n + sum(n + -1)
        }
    };
    sumX(sumX)
};
sum(10)
```

Unfortunately, this is an **infinite loop!**

We need to **delay** the evaluation of `sum` using the **η -expansion**:

$$e \equiv \lambda x.e(x) \quad \text{only if } x \text{ is NOT FREE in } e.$$

Recursion without New Syntax in FAE

```
/* FAE + conditionals */
val sum = {
    val sumX = sumY => {
        val sum = x => sumY(sumY)(x);
        n => { // EXACTLY the same as the original body
            if (n < 1) 0
            else n + sum(n + -1)
        }
    };
    sumX(sumX)
};
sum(10)
```

Recursion without New Syntax in FAE

```
/* FAE + conditionals */
val sum = {
    val sumX = sumY => {
        val sum = x => sumY(sumY)(x);
        n => { // EXACTLY the same as the original body
            if (n < 1) 0
            else n + sum(n + -1)
        }
    };
    sumX(sumX)
};
sum(10)
```

Do we need to do this for every recursive function?

Recursion without New Syntax in FAE

```
/* FAE + conditionals */
val sum = {
    val sumX = sumY => {
        val sum = x => sumY(sumY)(x);
        n => { // EXACTLY the same as the original body
            if (n < 1) 0
            else n + sum(n + -1)
        }
    };
    sumX(sumX)
};
sum(10)
```

Do we need to do this for every recursive function?

To avoid such boilerplate code, let's define a helper function `mkRec!`

Recursion without New Syntax in FAE

```
/* FAE + conditionals */
val sum = {
    val fX = fY => {
        val sum = x => fY(fY)(x);
        n => {
            if (n < 1) 0
            else n + sum(n + -1)
        }
    };
    fX(fX)
};
sum(10)
```

First, we rename `sumX` and `sumY` to `fX` and `fY`, respectively.

Recursion without New Syntax in FAE



```
/* FAE + conditionals */
val sum = {
    val fX = fY => {
        val sum = x => fY(fY)(x);
        n => {
            if (n < 1) 0
            else n + sum(n + -1)
        }
    };
    fX(fX)
};
sum(10)
```

Then, let's desugar the inside variable definition `sum`.

Recursion without New Syntax in FAE

```
/* FAE + conditionals */
val sum = {
    val fX = fY => {
        (sum => n => {
            if (n < 1) 0
            else n + sum(n + -1)
        })(x => fY(fY)(x))
    };
    fX(fX)
};
sum(10)
```

```
/* FAE + conditionals */
val sum = {
    val fX = fY => {
        (sum => n => {
            if (n < 1) 0
            else n + sum(n + -1)
        })(x => fY(fY)(x))
    };
    fX(fX)
};
sum(10)
```

Finally, let's define a helper function `mkRec` that takes a body of a recursive function and returns a recursive function.

mkRec: Helper Function for Recursion



```
/* FAE + conditionals */
val mkRec = body => {
    val fX = fY => body(x => fY(fY)(x))
    fX(fX)
};

val sum = mkRec(sum => n => {
    if (n < 1) 0
    else n + sum(n + -1)
});
sum(10)
```

```
/* FAE + conditionals */
val mkRec = body => {
    val fX = fY => body(x => fY(fY)(x))
    fX(fX)
};

val sum = mkRec(sum => n => {
    if (n < 1) 0
    else n + sum(n + -1)
});
sum(10)
```

Now, we can also define other recursive functions using `mkRec`.

mkRec: Helper Function for Recursion

```
/* FAE + conditionals */
val mkRec = body => {
    val fX = fY => body(x => fY(fY)(x))
    fX(fX)
};

val sum = mkRec(sum => n => {
    if (n < 1) 0
    else n + sum(n + -1)
});
sum(10)
```

Now, we can also define other recursive functions using `mkRec`. For example, the following recursive function `fac` computes the factorial:

```
/* FAE + conditionals */
val mkRec = ...;
val fac = mkRec(fac => n => if (n < 1) 1 else n * fac(n + -1));
fac(5) // 5 * 4 * 3 * 2 * 1 = 120
```

```
/* FAE + conditionals */  
body => {  
    val fX = fY => body(x => fY(fY)(x))  
    fX(fX)  
}
```

Its simplified version is as follows, and it is called the **Z combinator**:

```
/* FAE + conditionals */  
f => (x => f(v => x(x)(v))) (x => f(v => x(x)(v)))
```

²https://en.wikipedia.org/wiki/Fixed-point_combinator

```
/* FAE + conditionals */  
body => {  
    val fX = fY => body(x => fY(fY)(x))  
    fX(fX)  
}
```

Its simplified version is as follows, and it is called the **Z combinator**:

```
/* FAE + conditionals */  
f => (x => f(v => x(x)(v))) (x => f(v => x(x)(v)))
```

There are other **fixed-point combinators**² such as the **Y combinator** used in non-strict languages without η -expansion:

```
/* non-strict languages */  
f => (x => f(x(x))) (x => f(x(x)))
```

We will discuss non-strict (lazy) evaluation in the future.

²https://en.wikipedia.org/wiki/Fixed-point_combinator

Contents

1. Recursion and Conditionals

Recursion in F1VAE

Recursion in FAE

2. Recursion without New Syntax in FAE

`mkRec`: Helper Function for Recursion

3. RFAE – FAE with Recursion and Conditionals

Concrete Syntax

Abstract Syntax

4. Interpreter and Natural Semantics for RFAE

Interpreter and Natural Semantics

Arithmetic Comparison Operators

Conditionals

Recursive Function Definitions

The second way to support recursive functions in FAE is to extend FAE with **recursive function definitions**.

The second way to support recursive functions in FAE is to extend FAE with **recursive function definitions**.

RFAE is an extension of FAE with **recursion** and **conditionals**.

```
/* RFAE */  
def sum(n) = if (n < 1) 0 else n + sum(n + -1);  
sum(10) // 55
```

The second way to support recursive functions in FAE is to extend FAE with **recursive function definitions**.

RFAE is an extension of FAE with **recursion** and **conditionals**.

```
/* RFAE */  
def sum(n) = if (n < 1) 0 else n + sum(n + -1);  
sum(10) // 55
```

For RFAE, we need to extend **expressions** of FAE with

- ① **arithmetic comparison operators**
- ② **conditionals**
- ③ **recursive function definitions**

```
/* RFAE */  
def sum(n) = if (n < 1) 0 else n + sum(n + -1);  
sum(10) // 55
```

A **recursive function definition** consists of four parts:

- a function name
- a parameter name
- a function body expression
- a scope expression

```
/* RFAE */  
def sum(n) = if (n < 1) 0 else n + sum(n + -1);  
sum(10) // 55
```

A **recursive function definition** consists of four parts:

- a function name
- a parameter name
- a function body expression
- a scope expression

Note that a **recursive function definition** is also an expression can be used in any place where an expression is expected:

```
/* RFAE */  
2 * {  
    def sum(n) = if (n < 1) 0 else n + sum(n + -1);  
    sum(10) // 55  
} + 1 // 2 * 55 + 1 = 111
```

```
// expressions
<expr> ::= ...
    | <expr> "<" <expr>
    | "if" "(" <expr> ")" <expr> "else" <expr>
    | "def" <id> "(" <id> ")" "=" <expr> ";" <expr>
```

For RFAE, we need to extend **expressions** of FAE with

- ① **arithmetic comparison operators**
- ② **conditionals**
- ③ **recursive function definitions**

Abstract Syntax

Let's define the **abstract syntax** of RFAE in BNF:

Expressions $\mathbb{E} \ni e ::= \dots$

$e < e$	(Lt)
if (e) e else e	(If)
def $x(x) = e;$ e	(Rec)

Abstract Syntax

Let's define the **abstract syntax** of RFAE in BNF:

Expressions $\mathbb{E} \ni e ::= \dots$

$e < e$	(Lt)
$\text{if } (e) e \text{ else } e$	(If)
$\text{def } x(x) = e; e$	(Rec)

```
enum Expr:  
  ...  
  // less-than  
  case Lt(left: Expr, right: Expr)  
  // conditionals  
  case If(cond: Expr, thenExpr: Expr, elseExpr: Expr)  
  // recursive function definition  
  case Rec(name: String, param: String, body: Expr, scope: Expr)
```

Contents

1. Recursion and Conditionals

Recursion in F1VAE

Recursion in FAE

2. Recursion without New Syntax in FAE

`mkRec`: Helper Function for Recursion

3. RFAE – FAE with Recursion and Conditionals

Concrete Syntax

Abstract Syntax

4. Interpreter and Natural Semantics for RFAE

Interpreter and Natural Semantics

Arithmetic Comparison Operators

Conditionals

Recursive Function Definitions

Now, let's 1) implement the **interpreter**:

```
def interp(expr: Expr, env: Env): Value = ???
```

and 2) define the **natural semantics** for **recursive function definitions** and other new cases.

$$\sigma \vdash e \Rightarrow v$$

Expressions $\mathbb{E} \ni e ::= \dots$

$$\begin{array}{l|l} | \ e < e & (\text{Lt}) \\ | \ \text{if } (e) \ e \ \text{else } e & (\text{If}) \\ | \ \text{def } x(x) = e; \ e & (\text{Rec}) \end{array}$$

Values $\mathbb{V} \ni v ::= n \mid b \mid \langle \lambda x.e, \sigma \rangle$

```
enum Value:  
  case NumV(number: BigInt)  
  case BoolV(bool: Boolean)  
  case CloV(param: String, body: Expr, env: Env)
```

Arithmetic Comparison Operators

```
type BOp[T] = (T, T) => T
type COp[T] = (T, T) => Boolean
def numCOp(op: COp[BigInt], x: String): BOp[Value] =
  case (NumV(l), NumV(r)) => BoolV(op(l, r))
  case (l, r) => error(s"invalid operation: ${l.str} $x ${r.str}")

val numLt: BOp[Value] = numCOp(_ < _, "<")

def interp(expr: Expr, env: Env): Value = expr match
  ...
  case Lt(l, r) => numLt(interp(l, env), interp(r, env))
```

$$\boxed{\sigma \vdash e \Rightarrow v}$$

$$\text{Lt } \frac{\sigma \vdash e_1 \Rightarrow n_1 \quad \sigma \vdash e_2 \Rightarrow n_2}{\sigma \vdash e_1 < e_2 \Rightarrow n_1 < n_2}$$

Conditionals

```
def interp(expr: Expr, env: Env): Value = expr match
  ...
  case If(c, t, e) => interp(c, env) match
    case BoolV(true)  => interp(t, env)
    case BoolV(false) => interp(e, env)
    case v              => error(s"not a boolean: ${v.str}")
```

$$\sigma \vdash e \Rightarrow v$$

$$\text{If}_T \frac{\sigma \vdash e_0 \Rightarrow \text{true} \quad \sigma \vdash e_1 \Rightarrow v_1}{\sigma \vdash \text{if } (e_0) e_1 \text{ else } e_2 \Rightarrow v_1}$$

$$\text{If}_F \frac{\sigma \vdash e_0 \Rightarrow \text{false} \quad \sigma \vdash e_2 \Rightarrow v_2}{\sigma \vdash \text{if } (e_0) e_1 \text{ else } e_2 \Rightarrow v_2}$$

Recursive Function Definitions

```
def interp(expr: Expr, env: Env): Value = expr match
  ...
  case Rec(n, p, b, s) =>
    val newEnv: Env = ???  
    interp(s, newEnv)
```

$$\boxed{\sigma \vdash e \Rightarrow v}$$

$$\text{Rec } \frac{\sigma' = \text{???} \quad \sigma' \vdash e_3 \Rightarrow v_3}{\sigma \vdash \text{def } x_0(x_1) = e_2; e_3 \Rightarrow v_3}$$

Recursive Function Definitions

```
def interp(expr: Expr, env: Env): Value = expr match
  ...
  case Rec(n, p, b, s) =>
    val newEnv: Env = env + (n -> CloV(p, b, ???))
    interp(s, newEnv)
```

$$\boxed{\sigma \vdash e \Rightarrow v}$$

$$\text{Rec } \frac{\sigma' = \sigma[x_0 \mapsto \langle \lambda x_1. e_2, \text{???} \rangle] \quad \sigma' \vdash e_3 \Rightarrow v_3}{\sigma \vdash \text{def } x_0(x_1) = e_2; e_3 \Rightarrow v_3}$$

Recursive Function Definitions

```
def interp(expr: Expr, env: Env): Value = expr match
  ...
  case Rec(n, p, b, s) =>
    val newEnv: Env = env + (n -> CloV(p, b, newEnv)) // not working
    interp(s, newEnv)
```

$$\boxed{\sigma \vdash e \Rightarrow v}$$

$$\text{Rec } \frac{\sigma' = \sigma[x_0 \mapsto \langle \lambda x_1. e_2, \sigma' \rangle] \quad \sigma' \vdash e_3 \Rightarrow v_3}{\sigma \vdash \text{def } x_0(x_1) = e_2; e_3 \Rightarrow v_3}$$

```
def interp(expr: Expr, env: Env): Value = expr match
  ...
  case Rec(n, p, b, s) =>
    val newEnv: Env = env + (n -> CloV(p, b, newEnv)) // not working
    interp(s, newEnv)
```

$$\boxed{\sigma \vdash e \Rightarrow v}$$

$$\text{Rec } \frac{\sigma' = \sigma[x_0 \mapsto \langle \lambda x_1. e_2, \sigma' \rangle] \quad \sigma' \vdash e_3 \Rightarrow v_3}{\sigma \vdash \text{def } x_0(x_1) = e_2; e_3 \Rightarrow v_3}$$

While it makes sense in the natural semantics, the above Scala code doesn't work because `newEnv` is not yet defined.

```
def interp(expr: Expr, env: Env): Value = expr match
  ...
  case Rec(n, p, b, s) =>
    val newEnv: Env = env + (n -> CloV(p, b, newEnv)) // not working
    interp(s, newEnv)
```

$$\boxed{\sigma \vdash e \Rightarrow v}$$

$$\text{Rec} \frac{\sigma' = \sigma[x_0 \mapsto \langle \lambda x_1. e_2, \sigma' \rangle] \quad \sigma' \vdash e_3 \Rightarrow v_3}{\sigma \vdash \text{def } x_0(x_1) = e_2; e_3 \Rightarrow v_3}$$

While it makes sense in the natural semantics, the above Scala code doesn't work because `newEnv` is not yet defined.

Let's **delay** the evaluation of `newEnv` using the **η -expansion** again:

$$e \equiv \lambda x. e(x) \quad \text{only if } x \text{ is NOT FREE in } e.$$

We augment the closure value with an **environment factory** ($\lambda \Rightarrow \text{Env}$) rather than an **environment** (Env):

```
enum Value:
    ...
    case CloV(param: String, body: Expr, env: () => Env)

def interp(expr: Expr, env: Env): Value = expr match
    ...
    case Func(p, b) => CloV(p, b, () => env)
    case App(f, e) => interp(f, env) match
        case CloV(p, b, fenv) => interp(b, fenv() + (p -> interp(e, env)))
        case v                  => error(s"not a function: ${v.str}")
    case Rec(n, p, b, s) =>
        val newEnv: Env = env + (n -> CloV(p, b, () => newEnv)) // error
        interp(s, newEnv)
```

It still doesn't work because `newEnv` is not yet defined.

Let's use a **lazy value** (`lazy val`) to delay the evaluation of `newEnv`.

```
def interp(expr: Expr, env: Env): Value = expr match
  ...
  case Rec(n, p, b, s) =>
    lazy val newEnv: Env = env + (n -> CloV(p, b, () => newEnv))
    interp(s, newEnv)
```

$$\boxed{\sigma \vdash e \Rightarrow v}$$

$$\text{Rec} \frac{\sigma' = \sigma[x_0 \mapsto \langle \lambda x_1. e_2, \sigma' \rangle] \quad \sigma' \vdash e_3 \Rightarrow v_3}{\sigma \vdash \text{def } x_0(x_1) = e_2; e_3 \Rightarrow v_3}$$

We will learn more about **lazy values** in the later lectures in this course.

Exercise #5

<https://github.com/ku-plrg-classroom/docs/tree/main/cose212/rfae>

- Please see above document on GitHub:
 - Implement `interp` function.
- It is just an exercise, and you **don't need to submit** anything.
- However, some exam questions might be related to this exercise.

Summary

1. Recursion and Conditionals

Recursion in F1VAE

Recursion in FAE

2. Recursion without New Syntax in FAE

`mkRec`: Helper Function for Recursion

3. RFAE – FAE with Recursion and Conditionals

Concrete Syntax

Abstract Syntax

4. Interpreter and Natural Semantics for RFAE

Interpreter and Natural Semantics

Arithmetic Comparison Operators

Conditionals

Recursive Function Definitions

Next Lecture

- Mutable Data Structures

Jihyeok Park
jihyeok_park@korea.ac.kr
<https://plrg.korea.ac.kr>