

Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$



$w = \dots | B | a | b | b | B | B | B | B | \dots$

$f(w) = \dots | B | a | b | b | a | b | b | B | \dots$

- 1: **while** there are input symbols **do**
- 2: Find and Replace a (or b) with Z
- 3: Find and Fill the first blank with X (or Y) for a (or b)
- 4: Roll back Z to the original a (or b)
- 5: Replace X 's and Y 's with a's and b's
- 6: Go to the first input symbol

Construct a **Turing machine** that **computes** the function:



$$f(w \in \{a, b\}^*) = ww$$



Find and Replace a (or b) with Z.

Construct a **Turing machine** that **computes** the function:


$$f(w \in \{a, b\}^*) = ww$$



Find and Fill the first blank with X (or Y) for a (or 1).


Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$




Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$



Construct a **Turing machine** that **computes** the function:


$$f(w \in \{a, b\}^*) = ww$$



Roll back Z to the original a (or b).


Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$





Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$



Construct a **Turing machine** that **computes** the function:


$$f(w \in \{a, b\}^*) = ww$$



Repeat until no input symbols left.


Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$





Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$




Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$




Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$




Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$




Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$




Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$





Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$





Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$





Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$




Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$




Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$




Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$



Construct a **Turing machine** that **computes** the function:



$$f(w \in \{a, b\}^*) = ww$$



Replace X 's and Y 's with a 's and b 's.



Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$





Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$





Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$



Construct a **Turing machine** that **computes** the function:



$$f(w \in \{a, b\}^*) = ww$$



Go to the first input symbol.


Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$




Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$




Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$





Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$





Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$





Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$



Construct a **Turing machine** that **computes** the function:

$$f(w \in \{a, b\}^*) = ww$$



Computed! $f(abb) = abbabb$