

Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0, 1\}^*) = w + 1 \quad \text{where } w \text{ starts with 1}$$



$w = \dots | B | 1 | 0 | 1 | 0 | 1 | 1 | 1 | 1 | B | \dots$

$f(w) = \dots | B | 1 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | B | \dots$

- 1: Check if the first bit is 1.
- 2: Move to the end of the input.
- 3: Repeatedly replace the rightmost 1 with 0.
- 4: Replace 0 (or  $B$ ) with 1.
- 5: Go to the first input symbol.

Construct a **Turing machine** that **computes** the function:



$$f(w \in \{0, 1\}^*) = w + 1 \quad \text{where} \quad w \text{ starts with } 1$$



Check if the first bit is 1.

Construct a **Turing machine** that **computes** the function:



$$f(w \in \{0, 1\}^*) = w + 1 \quad \text{where} \quad w \text{ starts with } 1$$



Move to the end of the input.


Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0, 1\}^*) = w + 1 \quad \text{where } w \text{ starts with 1}$$




Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0, 1\}^*) = w + 1 \quad \text{where} \quad w \text{ starts with } 1$$





Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0, 1\}^*) = w + 1 \quad \text{where} \quad w \text{ starts with } 1$$





Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0, 1\}^*) = w + 1 \quad \text{where} \quad w \text{ starts with } 1$$





Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0, 1\}^*) = w + 1 \quad \text{where} \quad w \text{ starts with } 1$$





Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0, 1\}^*) = w + 1 \quad \text{where} \quad w \text{ starts with } 1$$



Construct a **Turing machine** that **computes** the function:


$$f(w \in \{0, 1\}^*) = w + 1 \quad \text{where} \quad w \text{ starts with } 1$$



Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0, 1\}^*) = w + 1 \quad \text{where} \quad w \text{ starts with } 1$$



...	B	1	0	1	0	1	1	1	1	B	...
-----	---	---	---	---	---	---	---	---	---	---	-----



Repeatedly replace the rightmost 1 with 0.



Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0, 1\}^*) = w + 1 \quad \text{where} \quad w \text{ starts with } 1$$




Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0, 1\}^*) = w + 1 \quad \text{where} \quad w \text{ starts with } 1$$




Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0, 1\}^*) = w + 1 \quad \text{where} \quad w \text{ starts with } 1$$



Construct a **Turing machine** that **computes** the function:



$$f(w \in \{0, 1\}^*) = w + 1 \quad \text{where} \quad w \text{ starts with } 1$$



Replace 0 (or  $B$ ) with 1.

Construct a **Turing machine** that **computes** the function:


$$f(w \in \{0, 1\}^*) = w + 1 \quad \text{where} \quad w \text{ starts with } 1$$



Go to the first input symbol.


Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0, 1\}^*) = w + 1 \quad \text{where} \quad w \text{ starts with } 1$$




Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0, 1\}^*) = w + 1 \quad \text{where} \quad w \text{ starts with } 1$$





Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0, 1\}^*) = w + 1 \quad \text{where} \quad w \text{ starts with } 1$$



Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0, 1\}^*) = w + 1 \quad \text{where } w \text{ starts with 1}$$



Computed!  $f(10101111) = 10110000$